



TIPO 13

Dimensiones (Milímetros)

A	B	C	M	N
±0.05	±0.05	±0.05	±0.05	±0.12
10	24.60	11.0	7.5	9
12	27.80	13.5	7.5	9
14	30.95	17.0	9.0	10.5
16	30.95	17.0	9.0	10.5
18	34.15	20.0	9.0	10.5
20	35.70	21.5	9.0	10.5
22	37.30	23.0	9.0	10.5
24	40.50	26.5	9.0	10.5
25	40.50	26.5	9.0	10.5
28	47.65	29.5	10.5	12.0
30	50.80	32.5	10.5	12.0
32	50.80	32.5	10.5	12.0
33	54.00	36.5	10.5	12.0
35	54.00	36.5	10.5	12.0
38	57.15	39.5	10.5	12.0
40	60.35	42.5	10.5	12.0
43	63.50	46.0	10.5	12.0
45	63.50	46.0	10.5	12.0
48	66.70	49.0	10.5	12.0
50	69.85	52.0	12.0	13.5
53	73.05	55.5	12.0	13.5
55	76.20	58.5	12.0	13.5
58	79.40	61.5	12.0	13.5
60	79.40	61.5	12.0	13.5
65	92.10	68.0	14.5	16.0
68	95.25	71.0	14.5	16.0
70	95.25	71.0	14.5	16.0
75	101.60	77.5	14.5	16.0
80	114.30	84.0	18.5	20.0



Materiales

-  Empaques > NBR (Nitrilo®), FKM (Viton®), E.P.R (EPDM)
-  Asientos > Acero Inoxidable, Carburo de Silicio, Carbon Grafito

LIMITES DE TEMPERATURA

